



DATA SHEET



SUBER BY KOLMER COATING AND SEALANT

FEATURES		COLORS	CONTAINER	PACKAGING
<ul style="list-style-type: none"> • Waterproof waterproof coating for facades and roofs, thermal-acoustic insulation, sealant and adhesive, anti-humidity and anti-alitre. • Based on natural cork and acrylic copolymer dispersions, free from asphalt products. • Suitable for insulation and waterproofing of façades, terraces and other supports indoors and outdoors. 		K-P	12 kilos	1 unit for 12 kilos
		K-TR		
SURFACE	PREPARATION	DRYING	REPAINT	FINISH
OUTDOORS-INDOORS	CLEAN SUPPORT	6-10 HOURS	24-48 HOURS	PROJECTED CORK
THINNER	PERFORMANCE	DENSITY	WASHABILITY	SOLIDS CONTENT
WATER 100-125 ML	1.5-2.5 Kg/m ² in 2/3 hand	0.91 g/cc		45%

TECHNICAL DATA

Minimum / maximum application temperature: +7°C / +35°C
 Recommended layer thickness: +- 3 mm (según necesidad).
 It is estimated an energy saving between 20% and 40%.
 Maximum content COV: 19 g/l
 EU limit value of the product (cat.A/c): 40 g/l (2010)

PROPERTIES

- Excellent insulation. • Waterproof. • Good elasticity.
- High resistance. • Good performance. • Great washability.
- Easy application. • Not toxic. • Non-flammable.
- Great resistance to aging. • Good resistance to alkalinity.

INSTRUCTIONS

- The supports must be in good condition, clean and consistent.
- On metal surfaces add KOLMAN ANTIOXIDANT ADDITIVE to the coating and homogenize.
- For first hand and successive, apply SUBER by Kolmer diluted to 1 -2 % water, leaving the surface homogeneous.
- It is imperative that the first layer is completely dry, before applying new layers.
- Apply to gun with appropriate nozzle for this product, cleaning the tool immediately afterwards with water.
- This coating allows for a light transit.
- To improve transit, we recommend adding KOLMAN TRANSITABLE ADDITIVE, then finishing with several layers of KOLMAN NATURA PARQUET VARNISH in the water.

SURFACE PREPARATION

Mortars and concretes:

Unpainted Surfaces: Wait for 30 days for proper solidification, clean efflorescence, release agents, mold and moss, loose particles and dirt. Whenever necessary, open pore by sanding polished surfaces. Before applying the finish coat, it is recommended to seal with KOLMAN FIXING SEALER or KOLMAN ANTICARBONATING PRINT, as required.

Already painted surfaces: Remove any old or poorly adhered paint. If the surface does not have good adhesion, it should be sanded and primed if necessary. If there are molds or moss, they must be treated and eliminated. Check the compatibility of the support and existing paint with the new paint to be applied.

Plaster and gypsum:

Unpainted surfaces: Wait for 30 days for proper solidification/drying. Sanitize and clean the support, eliminating efflorescence and loose particles. Apply a sealant, fixative or anti-carbonation primer, if necessary. If the support is good enough, a first coat of the diluted finishing layer may suffice.

Already painted surfaces: Remove any old or poorly adhered paint. If the surface does not have good adhesion, it should be sanded and primed if necessary. If there are efflorescence, molds or moss, they must be treated and eliminated. Check the compatibility of the support and existing paint with the new paint to be applied.

Ferrous metal surfaces:

Unpainted surfaces: On iron or steel supports, sand and clean with a cloth moistened with solvent to remove oils and grease, as well as rust residues. Next, apply a layer of antioxidant primer, and finish with the chosen varnish, unless an antioxidant varnish is used and the primer is not necessary.

Already painted surfaces: Remove any old or poorly adhered paint. If old paint has been removed, proceed as on new surfaces. If it has not been removed, check the compatibility of the existing paint with the one to be used.

Non-ferrous surfaces with difficult adhesion:

Unpainted surfaces: For surfaces such as aluminum, stainless steel, brass, galvanized, PVC ..., in addition to cleaning with a cloth moistened with solvent to remove oils and greases, you must treat them with a specific primer (wash primer, multi-adherent primer, etc.) and then apply the chosen finishing product or use a multi-adherent finishing product or with direct adhesion on this type of supports. In case of rust spots, it is necessary to treat specifically with an antioxidant primer. Check the compatibility of the latter with the surface and apply the necessary layers of product.

Already painted surfaces: Remove any old or poorly adhered paint. If the surface does not have good adhesion, it must be sanded and primed if necessary. If rust is present, treat it and remove loose particles. Check the compatibility of the support and the existing paint with the paint to be used.

Wood:

Unpainted Surfaces: When treating the wood, make sure that it is dry enough, as excess moisture will cause adhesion flaws and/or coloring flaws when dyeing the wood since the pores are filled with water. The moisture content should not exceed 12% -15%, depending on the type of wood. For new woods, remove stains and dirt, let dry if wet and then sand. Apply a priming coat or sealer, sand and later apply at least two layers of finish (it is recommended to sand between each layer). It is important to take into account the direction of the grain, both when sanding and applying, which must be done in the same direction.

Already painted surfaces: On painted wood, if the paint is very deteriorated, the easiest is to strip and remove the old paint. If the old paint is in good condition, sanding the surface is enough. It is recommended to perform a test, applying the paint in a small area, to ensure that there is no incompatibility between the two painting systems and the paintings themselves (e.g. old solvent paint and new water paint or vice versa). It is recommended to sand between each layer.

Tiles:

Clean and degrease the surface to be painted, eliminating all dirt and grease, and apply a specific paint for tiles directly, without primer. Always perform an adhesion test to verify the compatibility of the support with the paint.

Other surfaces:

For other special surfaces, please check.

STORAGE

Protect the containers from extreme temperatures 0°C. / 40 °C.
Recommended storage time, no more than 1 year.

ENVIRONMENT

Containers and waste must be disposed of according to current legislation. Do not throw waste into drains, consider possible reuse

SAFETY

Keep out of the reach of children.
Do not drink, eat, or smoke during application.
In case of contact with eyes, wash off with plenty of water.
For more information, please check the product safety data sheet.



Ambikol :

Products under the Integral System of Quality, Environment and Prevention, ISO 9001 and ISO 14001.



CE (CE marking):

The certificate/CE marking may only be extended when the product is to be applied on concrete or facings indicated in the UNE EN 1504-2: 2005 standard, having previously requested the certificate/markings in the order. For further information: <http://www.asefapi.es/files/MARCADO-CE-RECUBRIM16.pdf>



INDUSTRIAS KOLMER S.A

Polígono Industrial Juncaril, Calle Loja. Parcelas 111A-112.

Albolote. Granada. ESPAÑA

Phone: +34 958 46 56 86 || Fax: +34 958 46 74 02.

kolmer@kolmersa.com || www.kolmer.es

*Margin of numerical data: +-20%