

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)



Version 1 Date of compilation: 11/03/2022

Version 11 (replaces version 10)

Revision date: 16/06/2023

Page 1 of 14

Print date: 10/04/2024

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING.

1.1 Product identifier.

Product Name: KOLMAN SYNTHETIC ENAMEL WHITE GLOSS
UFI: 7FR0-20QF-C00A-E5WU

1.2 Relevant identified uses of the substance or mixture and uses advised against.

Finishing layer for metal and wood

Uses advised against:

Uses other than those recommended.

1.3 Details of the supplier of the safety data sheet.

Company: **INDUSTRIAS KOLMER, S.A.**
Address: POLIGONO IND. JUNCARIL C/LOJA PARCELA 111A-112
City: 18220 - ALBOLOTE
Province: GRANADA
Telephone: 958465686
Fax: 958467402
E-mail: KOLMER@KOLMERSA.COM

1.4 Emergency telephone number: 958465686 (Only available during office hours; Monday-Friday; 07:00-15:00)

SECTION 2: HAZARDS IDENTIFICATION.

2.1 Classification of the substance or mixture.

In accordance with Regulation (EC) No 1272/2008:

Aquatic Chronic 3 : Harmful to aquatic life with long lasting effects.

Flam. Liq. 3 : Flammable liquid and vapour.

STOT RE 1 : Causes damage to organs through prolonged or repeated exposure.

STOT SE 3 : May cause drowsiness or dizziness.

2.2 Label elements.

Labelling in accordance with Regulation (EC) No 1272/2008:

Pictograms:



Signal Word:

Danger

Hazard statements:

H226 Flammable liquid and vapour.
H336 May cause drowsiness or dizziness.
H372 Causes damage to organs through prolonged or repeated exposure.
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements:

P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P103 Read carefully and follow all instructions.

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)



KOLMAN SYNTHETIC ENAMEL WHITE GLOSS

Version 1 Date of compilation: 11/03/2022

Version 11 (replaces version 10)

Revision date: 16/06/2023

Page 2 of 14

Print date: 10/04/2024

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P271	Use only outdoors or in a well-ventilated area.
P501	Dispose of contents / container to hazardous or special waste public collection point

EUH statements:

EUH208	Contains maleic anhydride. May produce an allergic reaction.
EUH208	Contains Neodecanoic acid, cobalt salt. May produce an allergic reaction.
EUH211	Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

Contains:

Hydrocarbons, C9, aromatics
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

2.3 Other hazards.

The mixture does not contain substances classified as PBT.
The mixture does not contain substances classified as vPvB.
The mixture does not contain any endocrine disrupting properties substances.

In normal use conditions and in its original form, the product itself does not involve any other risk for health and the environment.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS.

3.1 Substances.

Not applicable.

3.2 Mixtures.

Substances posing a danger to health or the environment in accordance with the Regulation (EC) No. 1272/2008, assigned a Community exposure limit in the workplace, and classified as PBT/vPvB or included in the Candidate List:

Identifiers	Name	Concentrate	(*)Classification - Regulation (EC) No 1272/2008	
			Classification	Specifics concentration limits and Acute toxicity estimate
CAS No: 64742-82-1 Registration No: 01-2119458049-33-XXXX	Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	10 - 20 %	Aquatic Chronic 2, H411 - Asp. Tox. 1, H304 - Flam. Liq. 3, H226 - STOT RE 1, H372 - STOT SE 3, H336	-
CAS No: 64742-48-9 Registration No: 01-2119463258-33-XXXX	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics	1 - 10 %	Asp. Tox. 1, H304 - Flam. Liq. 3, H226 - STOT SE 3, H336	-
CAS No: 128601-23-0 Registration No: 01-2119455851-35-XXXX	Hydrocarbons, C9, aromatics	2.5 - 10 %	Aquatic Chronic 2, H411 - Asp. Tox. 1, H304 - Flam. Liq. 3, H226 - STOT SE 3, H335 - STOT SE 3, H336	-

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)



KOLMAN SYNTHETIC ENAMEL WHITE GLOSS

Version 1 Date of compilation: 11/03/2022

Version 11 (replaces version 10)

Revision date: 16/06/2023

Page 3 of 14

Print date: 10/04/2024

Index No: 601-022-00-9 CAS No: 1330-20-7 EC No: 215-535-7 Registration No: 01-2119488216-32-XXXX	[1] xylene	0 - 10 %	Acute Tox. 4 *, H312 - Acute Tox. 4 *, H332 - Flam. Liq. 3, H226 - Skin Irrit. 2, H315	-
CAS No: 27253-31-2 EC No: 248-373-0 Registration No: 01-2119970733-31-XXXX	Neodecanoic acid, cobalt salt	0.1 - 1 %	Acute Tox. 4, H302 - Aquatic Chronic 3, H412 - STOT RE 1, H372 - Skin Sens. 1, H317	-
Index No: 607-195-00-7 CAS No: 108-65-6 EC No: 203-603-9 Registration No: 01-2119475791-29-XXXX	[1] 2-methoxy-1-methylethyl acetate	0 - 20 %	Flam. Liq. 3, H226 - STOT SE 3, H336	-
Index No: 607-096-00-9 CAS No: 108-31-6 EC No: 203-571-6 Registration No: 01-2119472428-31-XXXX	maleic anhydride	0 - 0.001 %	Acute Tox. 4, H302 - Eye Dam. 1, H318 - Resp. Sens. 1, H334 - STOT RE 1, H372 - Skin Corr. 1B, H314 - Skin Sens. 1A, H317	Skin Sens. 1A, H317: C ≥ 0,001 %
Index No: 602-034-00-7 CAS No: 95-50-1 EC No: 202-425-9 Registration No: 01-2119451167-40-XXXX	[1] 1,2-dichlorobenzene	0 - 0.25 %	Acute Tox. 4 *, H302 - Aquatic Acute 1, H400 - Aquatic Chronic 1, H410 - Eye Irrit. 2, H319 - STOT SE 3, H335 - Skin Irrit. 2, H315	-

(*): The complete text of the H phrases is given in section 16 of this Safety Data Sheet.

*, ***, See Regulation (EC) No. 1272/2008, Annex VI, section 1.2.

[1] Substance with a European Union exposure limit in the workplace (see section 8.1).

[2] Substance with a national workplace exposure limit (see section 8.1).

This mixture contains >=1% TiO2 CAS 13463-67-7; EC 236-675-5; Index No. 022-006-00-2. The Annex VI classification of titanium dioxide does not apply to this mixture according to its Note 10.

SECTION 4: FIRST AID MEASURES.

4.1 Description of first aid measures.

Delayed effects may occur after the exposure to the product.

Inhalation.

Take the victim into open air; keep them warm and calm. If breathing is irregular or stops, perform artificial respiration. Do not administer anything orally. If unconscious, place them in a suitable position and seek medical assistance.

Eye contact.

Remove contact lenses, if present and if it is easy to do. Wash eyes with plenty of clean and cool water for at least 10 minutes while pulling eyelids up, and seek medical assistance.

Skin contact.

Remove contaminated clothing. Wash skin vigorously with water and soap or a suitable skin cleaner. NEVER use solvents or thinners.

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)



KOLMAN SYNTHETIC ENAMEL WHITE GLOSS

Version 1 Date of compilation: 11/03/2022

Version 11 (replaces version 10)

Revision date: 16/06/2023

Page 4 of 14

Print date: 10/04/2024

Ingestion.

If accidentally ingested, seek immediate medical attention. Keep calm. NEVER induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed.

Irritant Product, repeated or prolonged contact with skin or mucous membranes can cause redness, blisters or dermatitis, inhalation of spray mist or particles in suspension may cause irritation of the respiratory tract, some symptoms may not be immediate.

Long-term chronic exposure may result in injury to certain organs or tissues.

4.3 Indication of any immediate medical attention and special treatment needed.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious. Keep the person comfortable. Turn him/her over to the left side and stay there while waiting for medical care.

SECTION 5: FIREFIGHTING MEASURES.

Flammable product, the necessary prevention measures should be taken in order to avoid risks, In case of fire, the following measures are recommended:

5.1 Extinguishing media.

Suitable extinguishing media:

Extinguisher powder or CO2. In case of more serious fires, also alcohol-resistant foam and water spray.

Unsuitable extinguishing media:

Do not use a direct stream of water to extinguish. In the presence of electrical voltage, you cannot use water or foam as extinguishing media.

5.2 Special hazards arising from the substance or mixture.

Special risks.

Exposure to combustion or decomposition products can be harmful to your health.

During a fire and depending on its magnitude the following may occur:

- Flammable vapors or gases.

5.3 Advice for firefighters.

Use water to cool tanks, cisterns, or containers close to the heat source or fire. Take wind direction into account. Prevent the products used to fight the fire from going into drains, sewers, or waterways. Product residues and extinguishing media may contaminate the aquatic environment. Follow the instructions given in the emergency or fire evacuation plan or plans if available.

Fire protection equipment.

According to the size of the fire, it may be necessary to use protective suits against the heat, individual breathing equipment, gloves, protective goggles or facemasks, and boots. During extinction and depending on the magnitude and proximity to the fire, additional protective equipment such as chemical protection gloves, heat-reflecting suits or gas-tight suits may be required.

SECTION 6: ACCIDENTAL RELEASE MEASURES.

6.1 Personal precautions, protective equipment and emergency procedures.

Eliminate possible ignition points and ventilate the area. No smoking. Avoid breathing fumes. For exposure control and individual protection measures, see section 8.

6.2 Environmental precautions.

Product dangerous for the environment, in case of large spills or if the product contaminates lakes, rivers, or sewers, inform the responsible authorities according to local legislation. Prevent the contamination of drains, surface or subterranean waters, and the ground.

6.3 Methods and material for containment and cleaning up.

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)



KOLMAN SYNTHETIC ENAMEL WHITE GLOSS

Version 1 Date of compilation: 11/03/2022

Version 11 (replaces version 10)

Revision date: 16/06/2023

Page 5 of 14

Print date: 10/04/2024

Contain and collect spillage with inert absorbent material (earth, sand, vermiculite, Kieselguhr...) and clean the area immediately with a suitable decontaminant.

Deposit waste in closed and suitable containers for disposal, in compliance with local and national regulations (see section 13).

6.4 Reference to other sections.

For exposure control and individual protection measures, see section 8.

For later elimination of waste, follow the recommendations under section 13.

SECTION 7: HANDLING AND STORAGE.

7.1 Precautions for safe handling.

The fumes are heavier than air and can spread across the ground. They can form explosive mixtures with air. Prevent the creation of flammable or explosive fume concentrations in the air; prevent fume concentrations above work exposure limits. The product must only be used in areas where all unprotected flames and other ignition points have been eliminated. Electrical equipment has to be protected according to applicable standards.

The product can be electrostatically charged: always use earth grounds when transferring the product. Operators must use anti-static footwear and clothing, and floors must be conductors.

Keep the container tightly closed and isolated from heat sources, sparks, and fire. Do not use tools that can cause sparks. For personal protection, see section 8.

In the application area, smoking, eating, and drinking must be prohibited.

Follow legislation on occupational health and safety.

Never use pressure to empty the containers. They are not pressure-resistant containers. Keep the product in containers made of a material identical to the original.

7.2 Conditions for safe storage, including any incompatibilities.

Store according to local legislation. Observe indications on the label. Store the containers between 5 and 25 ° C, in a dry and well-ventilated place, far from sources of heat and direct solar light. Keep far away from ignition points. Keep away from oxidising agents and from highly acidic or alkaline materials. Do not smoke. Prevent the entry of non-authorized persons. Once the containers are open, they must be carefully closed and placed vertically to prevent spills.

The product is not affected by Directive 2012/18/EU (SEVESO III).

7.3 Specific end use(s).

Not available.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION.

8.1 Control parameters.

Work exposure limit for:

Name	CAS No.	Country	Limit value	ppm	mg/m ³
xylene	1330-20-7	European Union [1]	Eight hours	50 (skin)	221 (skin)
			Short term	100 (skin)	442 (skin)
2-methoxy-1-methylethyl acetate	108-65-6	European Union [1]	Eight hours	50 (skin)	275 (skin)
			Short term	100 (skin)	550 (skin)
1,2-dichlorobenzene	95-50-1	European Union [1]	Eight hours	20 (skin)	122 (skin)
			Short term	50 (skin)	306 (skin)

[1] According both Binding Occupational Exposure Limits (BOELVs) and Indicative Occupational Exposure Limits (IOELVs) adopted by Scientific Committee for Occupational Exposure Limits to Chemical Agents (SCOEL).

The product does NOT contain substances with Biological Limit Values.

Concentration levels DNEL/DMEL:

Name	DNEL/DMEL	Type	Value
xylene CAS No: 1330-20-7 EC No: 215-535-7	DNEL (Workers)	Inhalation, Chronic, Systemic effects	77 (mg/m ³)

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)



KOLMAN SYNTHETIC ENAMEL WHITE GLOSS

Version 1 Date of compilation: 11/03/2022

Version 11 (replaces version 10)

Revision date: 16/06/2023

Page 6 of 14

Print date: 10/04/2024

2-methoxy-1-methylethyl acetate CAS No: 108-65-6 EC No: 203-603-9	DNEL (Workers)	Inhalation, Chronic, Systemic effects	275 (mg/m ³)
	DNEL (Consumers)	Inhalation, Chronic, Systemic effects	33 (mg/m ³)
	DNEL (Workers)	Dermal, Chronic, Systemic effects	153,5 (mg/kg bw/day)
	DNEL (Consumers)	Dermal, Chronic, Systemic effects	54,8 (mg/kg bw/day)
	DNEL (Consumers)	Oral, Chronic, Systemic effects	1,67 (mg/kg bw/day)
maleic anhydride CAS No: 108-31-6 EC No: 203-571-6	DNEL (Workers)	Inhalation, Chronic, Local effects	0,4 (mg/m ³)
	DNEL (Workers)	Inhalation, Chronic, Systemic effects	0,4 (mg/m ³)
1,2-dichlorobenzene CAS No: 95-50-1 EC No: 202-425-9	DNEL (Workers)	Inhalation, Chronic, Local effects	200 (mg/m ³)
	DNEL (Workers)	Inhalation, Chronic, Systemic effects	59 (mg/m ³)

DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.

DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.

Concentration levels PNEC:

Name	Details	Value
2-methoxy-1-methylethyl acetate CAS No: 108-65-6 EC No: 203-603-9	aqua (freshwater)	0,635 (mg/L)
	aqua (marine water)	0,0635 (mg/L)
	aqua (intermittent releases)	6,35 (mg/L)
	STP	100 (mg/L)
	sediment (freshwater)	3,29 (mg/kg sediment dw)
	sediment (marine water)	0,329 (mg/kg sediment dw)
	soil	0,29 (mg/kg soil dw)

PNEC: Predicted No Effect Concentration, concentration of the substance below which adverse effects are not expected in the environmental compartment.

8.2 Exposure controls.

Measures of a technical nature:

Provide adequate ventilation, which can be achieved by using good local exhaust-ventilation and a good general exhaust system.

Concentration:	100 %
Uses:	Finishing layer for metal and wood
Breathing protection:	
PPE:	Filter mask for protection against gases and particles.
Characteristics:	«CE» marking, category III. The mask must have a wide field of vision and an anatomically designed form in order to be sealed and watertight.
CEN standards:	EN 136, EN 140, EN 405
Maintenance:	Should not be stored in places exposed to high temperatures and damp environments before use. Special attention should be paid to the state of the inhalation and exhalation valves in the face adaptor.
Observations:	Read carefully the manufacturer's instructions regarding the equipment's use and maintenance. Attach the necessary filters to the equipment according to the specific nature of the risk (Particles and aerosols: P1-P2-P3, Gases and vapours: A-B-E-K-AX), changing them as advised by the manufacturer.
Filter Type needed:	A2



-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)



KOLMAN SYNTHETIC ENAMEL WHITE GLOSS





Version 1 Date of compilation: 11/03/2022

Version 11 (replaces version 10)

Revision date: 16/06/2023

Page 7 of 14

Print date: 10/04/2024

Hand protection:			
PPE:	Non-disposable protective gloves against chemicals.		
Characteristics:	«CE» marking, category III. Check the list of chemicals for which the glove has been tested.		
CEN standards:	EN 374-1, EN 374-2, EN 374-3, EN 420		
Maintenance:	A schedule for the periodical replacement of gloves should be established in order to guarantee their replacement before pollutants permeate them. The use of contaminated gloves could be more dangerous than not using gloves, since the pollutant can gradually accumulate in the glove's material.		
Observations:	They are to be replaced whenever tears, cracks or deformations are observed or when exterior dirt could reduce their strength.		
Material:	PVC (polyvinyl chloride)	Breakthrough time (min.): > 480	Material thickness (mm): 0,35
Eye protection:			
PPE:	Protective goggles with built-in frame.		
Characteristics:	«CE» marking, category II. Eye protector with built-in frame for protection against dust, smoke, fog and vapour.		
CEN standards:	EN 165, EN 166, EN 167, EN 168		
Maintenance:	Visibility through lenses should be ideal. Therefore, these parts should be cleaned daily. Protectors should be disinfected periodically following the manufacturer's instructions.		
Observations:	Some signs of wear and tear include: yellow colouring of the lenses, superficial scratching of the lenses, scraping etc.		
Skin protection:			
PPE:	Chemical protective clothing		
Characteristics:	«CE» marking, category III. Clothing should fit properly. The level of protection must be set according to a test parameter called BT (Breakthrough Time), which indicates how long it takes for the chemical to pass through the material.		
CEN standards:	EN 464, EN 340, EN 943-1, EN 943-2, EN ISO 6529, EN ISO 6530, EN 13034		
Maintenance:	In order to guarantee uniform protection, follow the washing and maintenance instructions provided by the manufacturer.		
Observations:	The protective clothing's design should facilitate correct positioning, staying in place without moving for the period of use expected, bearing in mind environmental factors as well as any movement or position the user might adopt while carrying out the activity.		
PPE:	Anti-static safety footwear against chemicals.		
Characteristics:	«CE» marking, category III. Check the list of chemicals against which the footwear is resistant.		
CEN standards:	EN ISO 13287, EN 13832-1, EN 13832-2, EN 13832-3, EN ISO 20344, EN ISO 20345		
Maintenance:	For correct maintenance of this kind of safety footwear, it is necessary to observe the instructions specified by the manufacturer. The footwear should be replaced as soon as any sign of damage is observed.		
Observations:	The footwear should be cleaned regularly and dried when damp, although it should not be placed too close to a source of heat in order to avoid any sharp changes in temperature.		

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES.

9.1 Information on basic physical and chemical properties.

Physical state: Liquid

Colour: BLANCO

Odour: CARACTERISTICO

Odour threshold: Not applicable/Not available due to the nature/properties of the product

Melting point: Not applicable/Not available due to the nature/properties of the product

Freezing point: Not applicable/Not available due to the nature/properties of the product

Boiling point or initial boiling point and boiling range: 100 °C (Estimation based on the indication of the Regulation (CE) N°1272/2008.)

Flammability: Not applicable/Not available due to the nature/properties of the product

Lower explosion limit: Not applicable/Not available due to the nature/properties of the product

Upper explosion limit: Not applicable/Not available due to the nature/properties of the product

Flash point: 51 °C (Estimation based on the indication of the Regulation (CE) N°1272/2008.)

Auto-ignition temperature: Not applicable/Not available due to the nature/properties of the product

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)



KOLMAN SYNTHETIC ENAMEL WHITE GLOSS

Version 1 Date of compilation: 11/03/2022

Version 11 (replaces version 10)

Revision date: 16/06/2023

Page 8 of 14

Print date: 10/04/2024

Decomposition temperature: Not applicable/Not available due to the nature/properties of the product
pH: Not applicable (Substance/mixture is apolar/aprotic).
Kinematic viscosity: Not applicable/Not available due to the nature/properties of the product
Solubility: Not applicable/Not available due to the nature/properties of the product
Hydrosolubility: Not applicable/Not available due to the nature/properties of the product
Liposolubility: Not applicable/Not available due to the nature/properties of the product
Partition coefficient n-octanol/water (log value): Not applicable/Not available due to the nature/properties of the product
Vapour pressure: 16,096 (Estimation based on the indication of the Regulation (CE) N°1272/2008.)
Absolute density: 1192 kg/m³ (calculation/estimation)
Relative density: 1,192 g/cc (Pycnometer (ISO 758))
Relative vapour density: Not applicable/Not available due to the nature/properties of the product
Particle characteristics: Not applicable/Not available due to the nature/properties of the product

9.2 Other information

Information with regard to physical hazard classes

Flammable liquids:

Sustained combustibility: Yes.

SECTION 10: STABILITY AND REACTIVITY.

10.1 Reactivity.

The product does not present hazards by their reactivity.

10.2 Chemical stability.

Stable under the recommended handling and storage conditions (see section 7).

10.3 Possibility of hazardous reactions.

Flammable liquid and vapour.

10.4 Conditions to avoid.

Avoid any improper handling.

10.5 Incompatible materials.

Keep away from oxidising agents and from highly alkaline or acidic materials in order to prevent exothermic reactions.

10.6 Hazardous decomposition products.

No decomposition if used for the intended uses.

SECTION 11: TOXICOLOGICAL INFORMATION.

IRRITANT MIXTURE. The inhalation of spray mist or suspended particulates can irritate the respiratory tract. It can also cause serious respiratory difficulties, central nervous system disorders, and in extreme cases, unconsciousness.

11.1 Information on hazard classes as defined in Regulation (EC) N° 1272/2008.

Toxicological information about the substances present in the composition.

Name	Acute toxicity			
	Type	Test	Kind	Value
xylene	Oral	LD50	Rat	4300 mg/kg bw [1]
		[1] AMA Archives of Industrial Health. Vol. 14, Pg. 387, 1956		
	Dermal	LD50	Rabbit	> 1700 mg/kg bw [1]
[1] Raw Material Data Handbook, Vol.1: Organic Solvents, 1974. Vol. 1, Pg. 123, 1974				
CAS No: 1330-20-7 EC No: 215-535-7	Inhalation	LC50	Rat	21,7 mg/l/4 h [1]
		[1] Raw Material Data Handbook, Vol.1: Organic Solvents, 1974. Vol. 1, Pg. 123, 1974		

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)



KOLMAN SYNTHETIC ENAMEL WHITE GLOSS

Version 1 Date of compilation: 11/03/2022

Version 11 (replaces version 10)

Revision date: 16/06/2023

Page 9 of 14

Print date: 10/04/2024

2-methoxy-1-methylethyl acetate CAS No: 108-65-6 EC No: 203-603-9	Oral	LD50 Rat 6190 mg/kg bw [1] [1] Study report, 1985. OECD Guideline 401 (Acute Oral Toxicity).
	Dermal	LD50 Rabbit >5000 mg/kg bw [1] [1] Dow Chemical Company Reports. Vol. MSD-1582
	Inhalation	LC0 Rat >4345 ppm (6 h) [1] [1] Study report, 1980. OECD Guideline 403 (Acute Inhalation Toxicity).

a) acute toxicity;

Not conclusive data for classification.

b) skin corrosion/irritation;

Based on available data, the classification criteria are not met.

c) serious eye damage/irritation;

Based on available data, the classification criteria are not met.

d) respiratory or skin sensitisation;

Based on available data, the classification criteria are not met.

e) germ cell mutagenicity;

Not conclusive data for classification.

f) carcinogenicity;

Not conclusive data for classification.

g) reproductive toxicity;

Not conclusive data for classification.

h) STOT-single exposure;

Product classified:

Specific target organ toxicity following a single exposure, Category 3: May cause drowsiness or dizziness.

i) STOT-repeated exposure;

Product classified:

Specific target organ toxicity following a repeated exposure, Category 1: Causes damage to organs through prolonged or repeated exposure.

j) aspiration hazard;

Based on available data, the classification criteria are not met.

11.2 Information on other hazards.

Endocrine disrupting properties

This product does not contain components with endocrine-disrupting properties with effects on human health.

Other information

There is no information available on other adverse health effects.

SECTION 12: ECOLOGICAL INFORMATION.

12.1 Toxicity.

Name	Ecotoxicity			
	Type	Test	Kind	Value
xylene	Fish	LC50	Fish	15,7 mg/l (96 h) [1]

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)



KOLMAN SYNTHETIC ENAMEL WHITE GLOSS

Version 1 Date of compilation: 11/03/2022

Version 11 (replaces version 10)

Revision date: 16/06/2023

Page 10 of 14

Print date: 10/04/2024

CAS No: 1330-20-7 EC No: 215-535-7		[1] Bailey, H.C., D.H.W. Liu, and H.A. Javitz 1985. Time/Toxicity Relationships in Short-Term Static, Dynamic, and Plug-Flow Bioassays. In: R.C.Bahner and D.J.Hansen (Eds.), Aquatic Toxicology and Hazard Assessment, 8th Symposium, ASTM STP 891, Philadelphia, PA :193-212
	Aquatic invertebrates	LC50 Crustacean 8,5 mg/l (48 h) [1] [1] Tatem, H.E., B.A. Cox, and J.W. Anderson 1978. The Toxicity of Oils and Petroleum Hydrocarbons to Estuarine Crustaceans. Estuar.Coast.Mar.Sci. 6(4):365-373. Tatem, H.E. 1975. The Toxicity and Physiological Effects of Oil and Petroleum Hydrocarbons on Estuarine Grass Shrimp Palaemonetes pugio (Holthuis). Ph.D.Thesis, Texas A&M University, College Station, TX :133 p
	Aquatic plants	
2-methoxy-1-methylethyl acetate CAS No: 108-65-6 EC No: 203-603-9	Fish	LC50 Oryzias latipes 100 mg/L (96 h) [1] [1] Environment Agency of Japan (1998)
	Aquatic invertebrates	EC50 Daphnia magna 407 mg/L (48 h) [1] [1] Environment Agency of Japan (1998)
	Aquatic plants	EC50 Selenastrum capricornutum (Pseudokirchnerella subcapitata) >1000 mg/L (72 h) [1] [1] Environment Agency of Japan (1998)

12.2 Persistence and degradability.

No information is available regarding the biodegradability of the substances present.

No information is available on the degradability of the substances present.

No information is available about persistence and degradability of the product.

12.3 Bioaccumulative potential.

Information about the bioaccumulation of the substances present.

Name	Bioaccumulation			
	Log Pow	BCF	NOECs	Level
1,2-dichlorobenzene CAS No: 95-50-1 EC No: 202-425-9	3,43	-	-	Moderate

12.4 Mobility in soil.

No information is available about the mobility in soil.

The product must not be allowed to go into sewers or waterways.

Prevent penetration into the ground.

12.5 Results of PBT and vPvB assessment.

No information is available about the results of PBT and vPvB assessment of the product.

12.6 Endocrine disrupting properties.

This product doesn't contain components with environmental endocrine disrupting properties.

12.7 Other adverse effects.

The product is not affected by the Regulation (EC) No 1005/2009 of the European Parliament and of the Council of 16 September 2009 on substances that deplete the ozone layer.

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)



KOLMAN SYNTHETIC ENAMEL WHITE GLOSS

Version 1 Date of compilation: 11/03/2022

Version 11 (replaces version 10)

Revision date: 16/06/2023

Page 11 of 14

Print date: 10/04/2024

No information is available about other adverse effects for the environment.

SECTION 13: DISPOSAL CONSIDERATIONS.

13.1 Waste treatment methods.

Do not dump into sewers or waterways. Waste and empty containers must be handled and eliminated according to current, local/national legislation.

Follow the provisions of Directive 2008/98/EC regarding waste management.

SECTION 14: TRANSPORT INFORMATION.

Transport following ADR rules for road transport, RID rules for railway, ADN for inner waterways, IMDG for sea, and ICAO/IATA for air transport.

Land: Transport by road: ADR, Transport by rail: RID.

Transport documentation: Consignment note and written instructions

Sea: Transport by ship: IMDG.

Transport documentation: Bill of lading

Air: Transport by plane: ICAO/IATA.

Transport document: Airway bill.

14.1 UN number or ID number.

UN No: UN1263

14.2 UN proper shipping name.

Description:

ADR/RID: UN 1263, PAINT, 3, PG III, (D/E)

IMDG: UN 1263, PAINT, 3, PG III

ICAO/IATA: UN 1263, PAINT, 3, PG III

14.3 Transport hazard class(es).

Class(es): 3

14.4 Packing group.

Packing group: III

14.5 Environmental hazards.

Marine pollutant: No

Transport by ship, FEm – Emergency sheets (F – Fire, S - Spills): F-E,S-E

14.6 Special precautions for user.

Labels: 3



Hazard number: 30

Provisions concerning carriage in bulk ADR: Not authorized carriage in bulk in accordance with ADR.

Proceed in accordance with point 6.

ADR LQ: 5 L

IMDG LQ: 5 L

ICAO LQ: 10 L

14.7 Maritime transport in bulk according to IMO instruments.

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)



KOLMAN SYNTHETIC ENAMEL WHITE GLOSS

Version 1 Date of compilation: 11/03/2022

Version 11 (replaces version 10)

Revision date: 16/06/2023

Page 12 of 14

Print date: 10/04/2024

The product is not transported in bulk.

SECTION 15: REGULATORY INFORMATION.

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture.

Volatile organic compound (VOC)

Product Subcategory (Directive 2004/42/EC): d - Interior/exterior trim and cladding paints for wood and metal, solvent-borne

Phase I* (from 01/01/2007): 400 g/l

Phase II* (from 01/01/2010): 300 g/l

(*) g/l ready to use

VOC content (p/p): 22,778 %

VOC content: 271,513 g/l

The provisions of Directive 2004/42/EC on VOC apply to this product. Refer to the product label and/or technical data sheet for further information.

The product is not affected by Regulation (EU) No 528/2012 concerning the making available on the market and use of biocidal products.

The product is not affected by the procedure established Regulation (EU) No 649/2012, concerning the export and import of dangerous chemicals.

Restrictions on the manufacturing, placing on the market and use of certain dangerous substances, mixtures and articles:

Designation of the substance, of the group of substances or of the mixture	Conditions of restriction
3. Liquid substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: (a) hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F; (b) hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10; (c) hazard class 4.1; (d) hazard class 5.1.	1. Shall not be used in: - ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays, - tricks and jokes, - games for one or more participants, or any article intended to be used as such, even with ornamental aspects, 2. Articles not complying with paragraph 1 shall not be placed on the market. 3. Shall not be placed on the market if they contain a colouring agent, unless required for fiscal reasons, or perfume, or both, if they: - can be used as fuel in decorative oil lamps for supply to the general public, and, - present an aspiration hazard and are labelled with H304, 4. Decorative oil lamps for supply to the general public shall not be placed on the market unless they conform to the European Standard on Decorative oil lamps (EN 14059) adopted by the European Committee for Standardisation (CEN). 5. Without prejudice to the implementation of other Community provisions relating to the classification, packaging and labelling of dangerous substances and mixtures, suppliers shall ensure, before the placing on the market, that the following requirements are met: (a) lamp oils, labelled with H304, intended for supply to the general public are visibly, legibly and indelibly marked as follows: 'Keep lamps filled with this liquid out of the reach of children'; and, by 1 December 2010, 'Just a sip of lamp oil - or even sucking the wick of lamps - may lead to life-threatening lung damage'; (b) grill lighter fluids, labelled with H304, intended for supply to the general public are legibly and indelibly marked by 1 December 2010 as follows: 'Just a sip of grill lighter may lead to life threatening lung damage'; (c) lamp oils and grill lighters, labelled with H304, intended for supply to the general public are packaged in black opaque containers not exceeding 1 litre by 1 December 2010.

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)



KOLMAN SYNTHETIC ENAMEL WHITE GLOSS

Version 1 Date of compilation: 11/03/2022

Version 11 (replaces version 10)

Revision date: 16/06/2023

Page 13 of 14

Print date: 10/04/2024

15.2 Chemical safety assessment.

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

SECTION 16: OTHER INFORMATION.

Complete text of the H phrases that appear in section 3:

H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H372	Causes damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Classification codes:

Acute Tox. 4 : Acute toxicity (Dermal), Category 4
Acute Tox. 4 : Acute toxicity (Inhalation), Category 4
Acute Tox. 4 : Acute toxicity (Oral), Category 4
Aquatic Acute 1 : Acute toxicity to the aquatic environment, Category 1
Aquatic Chronic 1 : Chronic effect to the aquatic environment, Category 1
Aquatic Chronic 2 : Chronic effect to the aquatic environment, Category 2
Aquatic Chronic 3 : Chronic effect to the aquatic environment, Category 3
Asp. Tox. 1 : Aspiration toxicity, Category 1
Eye Dam. 1 : Serious eye damage, Category 1
Eye Irrit. 2 : Eye irritation, Category 2
Flam. Liq. 3 : Flammable liquid, Category 3
Resp. Sens. 1 : Respiratory sensitiser, Category 1
STOT RE 1 : Specific target organ toxicity following a repeated exposure, Category 1
STOT SE 3 : Specific target organ toxicity following a single exposure, Category 3
Skin Corr. 1B : Skin Corrosive, Category 1B
Skin Irrit. 2 : Skin irritant, Category 2
Skin Sens. 1 : Skin sensitiser, Category 1
Skin Sens. 1A : Skin sensitiser, Category 1A

Changes regarding to the previous version:

- Changes in the information of the supplier (SECTION 1.3).
- Change in the emergency number (SECTION 1.4).
- Change in the hazard classification (SECTION 2.1).
- Removal of precautionary statements/hazard statements/pictograms/signal word (SECTION 2.2).
- Addition of precautionary statements/hazard statements/pictograms/signal word (SECTION 2.2).
- Changes in the composition of the product (SECTION 3.2).
- Changes in the composition of the product (SECTION 3.2).
- Changes in the composition of the product (SECTION 3.2).
- Modification of the symptoms (SECTION 4.2).

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)



KOLMAN SYNTHETIC ENAMEL WHITE GLOSS

Version 1 Date of compilation: 11/03/2022

Version 11 (replaces version 10)

Revision date: 16/06/2023

Page 14 of 14

Print date: 10/04/2024

- Modifications in the handling and storage precautions (SECTION 7.1).
- Modifications in the handling and storage precautions (SECTION 7.2).
- Elimination of exposure data (SECTION 8.1).
- Addition of exposure data (SECTION 8.1).
- Modification in the values of the physical and chemical properties (SECTION 9).
- Modification of the information of the stability and reactivity conditions (SECTION 10.1).
- Modification of the information of the stability and reactivity conditions (SECTION 10.4).
- Modification of the information of the stability and reactivity conditions (SECTION 10.5).
- Modification of the information of the stability and reactivity conditions (SECTION 10.6).
- Change in the hazard classification (SECTION 11.1).
- Addition of ecological information values (SECTION 12.3).
- National legislative changes (SECTION 15.1).
- Elimination of abbreviations and acronyms (SECTION 16).

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Physical hazards	On basis of test data
Health hazards	Calculation method
Environmental hazards	Calculation method

It is advisable to carry out basic training with regard to health and safety at work in order to handle this product correctly.

Abbreviations and acronyms used:

ADR:	Agreement concerning the International Carriage of Dangerous Goods by Road.
BCF:	Bioconcentration factor.
CEN:	European Committee for Standardization.
DMEL:	Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.
DNEL:	Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.
EC50:	Half maximal effective concentration.
PPE:	Personal protection equipment.
IATA:	International Air Transport Association.
ICAO:	International Civil Aviation Organization.
IMDG:	International Maritime Code for Dangerous Goods.
LC50:	Lethal concentration, 50%.
LD50:	Lethal dose, 50%.
NOEC:	No observed effect concentration.
PNEC:	Predicted No Effect Concentration, concentration of the substance below which adverse effects are not expected in the environmental compartment.
RID:	Regulations Concerning the International Transport of Dangerous Goods by Rail.

Key literature references and sources for data:

<http://eur-lex.europa.eu/homepage.html>

<http://echa.europa.eu/>

Regulation (EU) 2020/878.

Regulation (EC) No 1907/2006.

Regulation (EC) No 1272/2008.

The information given in this Safety Data Sheet has been drafted in accordance with COMMISSION REGULATION (EU) 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemical substances and mixtures (REACH).

The information in this Safety Data Sheet on the Preparation is based on current knowledge and on current EC and national laws, as far as the working conditions of the users is beyond our knowledge and control. The product must not be used for purposes other than those that are specified without first having written instructions on how to handle. It is always the responsibility of the user to take the appropriate measures in order to comply with the requirements established by current legislation. The information contained in this Safety Sheet only states a description of the safety requirements for the preparation, and it must not be considered as a guarantee of its properties.

-End of safety data sheet.-